

GEOTECHNICAL ENGINEERING REPORT

AIMRIGHT Project No. 13320723

August 10, 2023

Spavinaw 54-inch Lift Station

Prepared for:

BKL, Inc.



Construction Materials Testing • Special Inspections • Geotechnical Engineering

August 10, 2023

BKL, Inc.
1623 E 6th St
Tulsa, OK 74120
(918) 835-9588

Attn: Stacy Loeffler, P.E., President, loeffler@bklinc.com


Re: Geotechnical Engineering Report | No. 13320723
Spavinaw 54-inch Lift Station
[555 N Main St, Spavinaw, OK 74366](#)

It has been a pleasure serving you on this project. AIMRIGHT is pleased to submit this Geotechnical Engineering Report for the proposed construction planned at the referenced site. This report presents the findings of the geotechnical exploration and presents recommendations for design for the project.

We appreciate the opportunity to provide geotechnical consultation services for the subject project. We look forward to serving as your geotechnical engineer and construction materials testing laboratory on the remainder of this and future projects. Please do not hesitate to contact us with any concerns or questions regarding this report.

Respectfully submitted,

AIMRIGHT Testing & Engineering, LLC
CA No. 5794 (exp. 6/30/24)
Justin J. Boyd Jr., P.E.
Engineering Manager
jboyd@aimrighttesting.com
(918) 392-8041



A handwritten signature in blue ink that reads "Justin J. Boyd Jr." written over the bottom portion of the professional seal.

TABLE OF CONTENTS

1.0 PROJECT INFORMATION	1
1.1 Description	1
1.2 Scope of Services	1
1.3 Field Exploration	2
1.4 Laboratory Testing	2
2.0 FIELD EXPLORATION FINDINGS	3
2.1 Subsurface	3
2.2 Groundwater	3
3.0 LABORATORY TESTING RESULTS	4
4.0 ANALYSIS & CONCLUSIONS	5
5.0 RECOMMENDATIONS	6
5.1 Site Preparation and Earthwork	6
5.2 Potential Excavation Difficulties	7
5.3 Site Drainage	8
5.4 Fill Material	9
5.5 Shallow Foundation Design	10
5.6 Shallow Foundation Construction	11
5.7 Slab-on-ground Design	12
5.8 Excavations Adjacent to Existing Structures	13
5.9 Lateral Earth Pressure Parameters	14
6.0 CONSTRUCTION MONITORING	15
7.0 LIMITATIONS	16
APPENDIX	
Boring Location Plans	
Boring Logs	
Boring Log Key to Symbols	

1.0 PROJECT INFORMATION

1.1 Description

We understand that a new one-story structure addition will be constructed on the referenced site. The site is currently developed with existing structure, above/below-grade infrastructure, and mainly grass/soil covered. The final site design has not been completed.

It is our understanding the existing building and dam structures were constructed on varying depths of fill or backfill as well as varying fill materials. Construction monitoring/testing documentation of the fill placement was not provided and likely not available.

The site is generally level with minimal elevation differences across the planned construction footprint. Cut/fill depths have not been finalized; however, we estimate that cut of approximately 6 to 12 inches (south end) and approximately 3 to 10+ feet (north end into slope area) will be required to reach the final site elevations.

The structure is anticipated to likely be comprised of metal/CMU framing and supported by a concrete slab-on-ground and shallow foundation system (with concrete/CMU stem walls). Information regarding estimated structural loading conditions was not provided; however, we will utilize maximum column loads of 10 to 20 kip, and wall loads of 1 to 2 kip per linear foot in our engineering analyses.

1.2 Scope of Services

The primary purpose of this report is to provide geotechnical engineering recommendations for the proposed site development. Our Scope of Services consisted of the following:

- Drilling two (2) soil test borings (borings) to depths of approximately 20 feet, or auger refusal, whichever occurred first.
- Performing laboratory testing of selected soil samples obtained from the borings.
- Providing engineering analysis and preparation of this report discussing, in general, project description, our scope, exploration, testing, analysis, and recommendations.

The Boring Location Plans, Boring Logs, and other supporting data are presented in the Appendices to this report. Our Scope of Services did not include a survey of boring locations and elevations, rock coring, quantity estimates, preparation of plans or specifications, slope stability analysis, or the identification and evaluation of environmental aspects of the project site.

1.3 Field Exploration

AIMRIGHT located the borings in the field by making measurements from known existing site features. No claim is made as to the accuracy of the locations shown on the Boring Location Plans, and they should be considered approximate.

The borings were advanced using an ATV-mounted drill rig equipped with an automatic hammer and 6-inch diameter augers. Representative soil samples were obtained using a standard 2-inch outside diameter split-barrel sampler in general compliance with the Standard Penetration Testing (SPT) method of the American Society of Testing and Materials (ASTM) D1586 standard to evaluate the consistency and general engineering properties of the subsurface soils.

The number of blows required to drive the split-barrel sampler three (3) consecutive 6-inch increments is recorded, and the blows of the last two 6-inch increments are added to obtain the SPT N-value in blows per foot (bpf) representing the penetration resistance of the soil. At regular intervals within the borings, split-spoon samples were visually classified based on texture and plasticity.

During the drilling process, all encounters with groundwater, if any, were recorded. Upon completion of drilling, all borings were backfilled per OWRB requirements.

1.4 Laboratory Testing

The samples obtained from the geotechnical exploration were transported to the AIMRIGHT laboratory where representative samples were selected for testing. Testing consisted of Atterberg limits, sieve analysis, and determination of moisture content in general accordance with the ASTM testing procedures.

2.0 FIELD EXPLORATION FINDINGS

2.1 Subsurface

The subsurface conditions illustrated in the table below represent an estimate of the subsurface conditions based on interpretation of the boring data using normally accepted geotechnical engineering judgments. The transitions between soil strata are usually less distinct than shown on the Boring Logs.

Stratum	General Depth Interval	General Description of Conditions
Surface	2 to 6 inches	organic laden soils (topsoil) sampled as silty sand/sandy silt with organics and root matter
	12 to 16 inches	aggregate base
Native Soils	0 to 16 feet	very loose to medium dense sand with varying amounts of silt, clay, sand, and gravel, chert/limestone fragments
Rock	6 to 16 feet	hard limestone

Auger refusal was encountered in boring B-1 and B-2 at depths of approximately 6 to 16.25 feet, respectively. Auger refusal is defined as material that could not be penetrated with the drill rig equipment used on the project. Auger refusal material may be caused by rock, large boulders, rock ledges, lenses, seams, or the top of parent bedrock.

2.2 Groundwater

Groundwater was not encountered during or at the completion of drilling in any of the borings. Water traveling through soil and rock is often unpredictable and may be present at shallow depths. Due to the seasonal changes in groundwater and the unpredictable nature of groundwater paths, groundwater levels will fluctuate. As such, groundwater levels at other times of the year may be different than those described in this report.

Generally, the highest groundwater levels occur in late winter and early spring and the lowest levels in late summer and fall. Therefore, it is necessary during construction to be observant for groundwater seepage in excavations to assess the situation and make necessary changes. Where applicable, the contractor should determine the actual groundwater levels at the time of construction.

3.0 LABORATORY TESTING RESULTS

Laboratory tests were conducted on selected samples in general accordance with ASTM standards. The laboratory testing performed for this project consisted of Atterberg Limits (ASTM D4318), Moisture Content (ASTM D2216) and Sieve Analysis – No. 200 Sieve Wash Method (ASTM D1140) testing. The test results are presented on the Boring Logs and summarized in the table below.

Boring No.	Sample Depth Interval (ft)	In-place Moisture Content (%)	Finer than No. 200 Sieve (%)	Atterberg Limits		
				Liquid Limit (%)	Plastic Limit (%)	Plasticity Index
B-1	0 to 1.5	23.8	43.9	32	16	16
B-2	1.5 to 3	11.9	39.1	30	15	15
	6 to 7.5	9.0	39.2	30	15	15
	11 to 12.5	15.6	41.1	30	16	14

4.0 ANALYSIS & CONCLUSIONS

The following recommendations are based on our observations at the site, interpretation and analysis of the field and laboratory data obtained during this exploration, assumed loads, and our experience with previous exploration and testing with similar projects. Soil penetration data have been used to estimate an allowable bearing pressure and associated settlement using established correlations. Subsurface conditions in unexplored locations may vary from those encountered.

If structure location, loadings, or elevations are changed, we request that we be advised so that we may re-evaluate our recommendations. In the event changes are made in the proposed design/construction plans, the recommendations presented in this report shall not be considered valid unless reviewed by AIMRIGHT and modified or verified in writing.

Determination of an appropriate foundation system for a given structure is dependent on the proposed structural loads, soil conditions, and construction constraints such as proximity to other structures, etc. The subsurface exploration aids the geotechnical engineer in determining the soil stratum appropriate for structural support. This determination includes considerations regarding both allowable bearing pressure and compressibility of the soil strata. In addition, since the method of construction greatly affects the soils intended for structural support, consideration must be given to the implementation of suitable methods of site preparation, fill compaction, and other aspects of construction.

In conclusion, provided the recommendations outlined in this report are followed throughout the design and construction phases of this project, it is our opinion that the site is suitable for the planned development and a concrete slab-on-ground in conjunction with a shallow foundation design may be utilized to support the structure.

It is imperative that all exposed foundation subgrades be re-compacted, observed, evaluated, and verified for the design soil bearing pressure by the geotechnical engineer after excavation and prior to concrete placement. This evaluation should include, as a minimum, Dynamic Cone Penetrometer (DCP) testing at the planned bearing elevations at intervals of no less than 35 feet and extending to depths of at least 3 feet below the bearing elevations.

5.0 RECOMMENDATIONS

5.1 Site Preparation and Earthwork

Before proceeding with construction, AIMRIGHT recommends conducting a pre-grading meeting to discuss recommendations as outlined in this report.

Where appropriate, existing utilities beneath the construction footprints should be properly abandoned; or, should be removed and backfilled with properly compacted engineered fill as outlined in this report.

Any existing topsoil/vegetation, wet, soft, or loose soils and any other deleterious non-soil materials should be removed to a minimum distance of 5 feet beyond the structure footprints.

Upon completion of required excavations, proof-rolling of the subgrade with a 20 to 30-ton loaded truck or other pneumatic-tired vehicle of similar size and weight should then be performed. Proof-rolling should be performed during a time of good weather and not while the site is wet, frozen, or severely desiccated.

Unsuitable near surface soil conditions should be anticipated within some areas. All unsuitable materials observed during the evaluation and proof-rolling operations should be over-excavated and replaced with compacted fill or stabilized in place. The possible need for, and extent of over-excavation and/or in-place stabilization required can best be determined by the geotechnical engineer at that time.

The upper 8 inches of the existing subgrade in construction areas shall then be scarified, moisture-conditioned and re-compacted to at least ninety-five percent (95%) of the maximum dry density and within ± 2 percentage points of the optimum moisture content as determined by a Standard Proctor (ASTM D698). The moisture content and compaction shall be maintained prior to beginning any fill or aggregate placement and/or construction.

At the time of the investigation, the site soils were generally moist. If dry weather conditions exist prior to and during construction, the near surface soils may need moisture-conditioning to sufficiently enable adequate scarifying and compaction. However, if wet conditions exist at the time of construction, then care shall be taken to assure proper surface water drainage. If these soils do get wet, they must be dried or treated prior to further compaction efforts.

We note that some of the near surface materials (i.e., silty clayey sand, sandy silt, silty clay, silt, etc.) will often exhibit shearing as open subgrades under wheel loads and will not hold up well to construction activities, especially during wet periods. A layer of aggregate base or crushed stone quickly placed after subgrade preparation and verification will help confine the subgrade soils and reduce imminent disturbance from construction activities.

5.2 Potential Excavation Difficulties

Hard limestone was encountered in the borings beginning at depths of approximately 6 and 16 feet. Auger refusal was encountered in boring B-1 and B-2 at depths of approximately 6 to 16.25 feet, respectively. Auger refusal material may be caused by rock, large boulders, rock ledges, lenses, seams, or the top of parent bedrock.

We anticipate the near-surface soils above these depths at the site can be excavated with pans, scrapers, backhoes, and front-end loaders using conventional means and methods.

Our experience indicates rock in a weathered, boulder, and/or massive form may vary erratically in location and depth within the referenced site. Therefore, there is always a potential that these materials could be encountered at shallower depths between the boring locations and should be anticipated during construction.

Installation or excavation of proposed subgrade, foundations, or underground utilities (depending on layout and planned bottom elevations) within some portions of the site will require jackhammering, coring, ripping, or other suitable methods to remove these materials.

5.3 Site Drainage

An important aspect to consider during development of this site is surface water control. During the initiation of grading operations, we recommend that the grading contractor take those steps necessary to enhance surface flow and promote rapid clearing of rainfall and runoff water following rain events.

It should be incumbent on the contractor to maintain favorable site drainage during construction to minimize deterioration of otherwise stable subgrades.

Permanent positive drainage should be provided around the perimeter of the structures to minimize moisture infiltration into the foundation and/or subgrade soils. We recommend landscaped areas adjacent to the structures be provided with a fall of at least 6 inches for the first 10 feet outward from the structure areas.

All grades must provide effective drainage away from the structures during and after construction. Water permitted to pond next to the structures can result in unacceptable differential floor slab movements and cracked slabs and/or walls.

After construction and landscaping, AIMRIGHT recommends verifying final grades to document that effective drainage has been achieved. Grades around the structures should also be periodically inspected and adjusted as necessary, as part of the structure's maintenance program.

Sprinkler mains and spray heads should be located a minimum of 5 feet away from the structure lines. Roof runoff should be collected in drains or gutters. Roof drains and downspouts should be discharged onto pavements which slope away from the structures or downspouts should be extended a minimum of 10 feet away from the structures.

5.4 Fill Material

A sample of each material type should be submitted to the geotechnical engineer for evaluation. Frozen material should not be used, and fill should not be placed on a frozen subgrade.

All fill material in structural areas (including utility backfill) should be placed in continuous, horizontal lifts having a maximum pre-compacted thickness of 9 inches. Aggregate base should have a maximum pre-compacted thickness of 6 inches; and fill compacted with hand-held or smaller-sized equipment having a maximum pre-compacted thickness of 4 to 6 inches.

Fill placed over existing slopes should be adequately benched or keyed into the existing slopes so that fill is not placed and/or compacted on a sloping subgrade or vertical wall excavation. The benches will help facilitate compaction, reduce the potential for high differential settlements over short distances, and increase the overall global stability of the constructed fill.

Each lift should be compacted to at least ninety-five percent (95%) of the maximum dry density and within ± 2 percentage points of the optimum moisture content as determined by a Standard Proctor (ASTM D698), unless noted otherwise and maintained throughout construction activities.

A minimum of two (2) field tests to determine in-place density and moisture content should be performed per lift for each 2,000 sf within structural footprints.

Engineered fill should consist of approved materials that are free of organic matter and debris, exhibit a maximum plasticity index (PI) of 18, maximum liquid limit (LL) of 40, and a maximum rock size of 3.0 inches.

Native soils could be used as fill; whereby, upon re-use, the soils meet the requirements for engineered fill as stated in this report. AIMRIGHT recommends conducting additional soil sampling and laboratory testing of any excavated or cut native soils to determine characteristics and stabilization requirements prior to beginning any fill placement.

5.5 Shallow Foundation Design

The project structural engineer should determine the final foundation sizes based on the actual design loads, building code requirements, and other structural considerations. Structure foundations may be designed utilizing the following parameters.


Maximum Structural Loads	Wall	1 to 2 kip/ft
	Column	10 to 20 kip
Bearing Material		approved native soils or engineered fill
Net Allowable Bearing Pressure¹ (FS ≥ 2.5)		2,000 psf
Coefficient of Sliding Friction², μ		0.28 to 0.37
Total Unit Weight², γ		100 to 115 pcf
Angle of Friction², ϕ		15°
Rankine Passive Earth Pressure Coefficient², K_p		1.69
Minimum Footing Embedment³		24 inches
Minimum Footing Width	Wall	18 inches
	Column	24 inches
Estimated Maximum Settlement⁴	Total	≤ 1 inch
	Differential	≤ ½ inch
Earthquake Loads Site Class⁵		D

1. The recommended net allowable bearing pressure is based on foundations within approved bearing materials and is the pressure more than the minimum surrounding overburden pressure at the footing base elevation.
2. Range of values provided for soil types encountered at the site that are prepared in accordance with this report are illustrated, however, actual parameters are dependent on bearing material placed and/or exposed during construction. Values are provided for guidance and should only be utilized by experienced engineers and designers. Exclude total passive pressure resistance within 2 feet of the adjacent lowest final site elevation.
3. Minimum depth applies to both perimeter footings and foundations in unheated areas. Minimum depth will provide frost protection and reduce the potential for moisture variation below the bearing level. Interior foundations should extend at least 12 inches below the final adjacent subgrade to provide minimum confinement.
4. The magnitude of the settlements will be highly influenced by the variation in excavation requirements across the structure footprint, the distribution of loads, and the variability of underlying soils.
5. 2018 International Building Code (IBC) Section 16, a weighted average of the soil penetration resistance conditions recorded (limited N-value of 100 bpf) and estimated for the upper 100 feet of the site was calculated.

5.6 Shallow Foundation Construction

All exposed foundation subgrades should be re-compacted, observed, evaluated, and verified for the design soil bearing pressure by the geotechnical engineer after excavation and prior to concrete placement. This evaluation should include, as a minimum, Dynamic Cone Penetrometer (DCP) testing at the planned bearing elevations at intervals of no less than 35 feet and extending to depths of at least 3 feet below the bearing elevations.

If unsuitable material is encountered during foundation bearing grade testing and inspections (DCP Testing), foundations should; 1) extend deeper to a more suitable bearing material and bear directly on this material; 2) extend deeper to a more suitable bearing material and backfill with lean concrete to the designed bottom of footing elevation (see Figure 1); 3) extend deeper to a more suitable bearing material and backfilled with engineered fill (see Figure 2). If option 3 is selected, the over-excavation should extend laterally a minimum of $2/3$ of the total depth of excavation.



Note: Figures are shown for convenience and excavations shall be conducted with appropriate safety requirements.

To reduce differential settlement, it is imperative to ensure that all shallow foundations bear on a minimum of 12 inches of similar material. Where applicable, to prevent a “point-load” bearing condition where the newly placed engineered fill or native soils adjoins weathered rock within wall/column footings, we recommend over-excavating the weathered rock to a minimum depth of 12 inches within the entire length of the wall/column footing and backfilling with properly compacted engineered fill. Alternatively, the engineered fill and/or native soils may be over-excavated down to the weathered rock and backfilled with lean concrete to the designed bearing elevation as illustrated in Figure 1 above.

Foundation excavations must be maintained in a drained/de-watered condition throughout the foundation construction process and water should not be allowed to pond in any excavation. Excavations for footings should be made in such a way as to provide bearing surfaces that are firm and free of loose, soft, wet, or otherwise disturbed soils. Foundations should be concreted as soon as practical after they are excavated, and concrete should also not be placed on frozen or saturated subgrades. When applicable, it is recommended that a 2 to 4-inch-thick “mud mat” of lean concrete be placed on the bearing soils to help protect the bearing surface from rainfall or adverse construction activities.

5.7 Slab-on-ground Design

The structure subgrades should be prepared as described in this report. Four (4) inches or more of granular base should be placed over the final soil subgrade and shall meet the requirements outlined in the table below. The modulus of subgrade reaction, k, value illustrated in the table below is based on 30-inch diameter plate load test.

Minimum Percent Finer than 1 ½-inch Sieve	Maximum Percent Finer than No. 200 Sieve	Maximum Plasticity Index	k w/ 4 inches of Granular Base (psi/in)	k w/ 8 inches of Granular Base (psi/in)
100	15	6	125	150

At the time of concrete placement, the granular base should be moist, but free of any self-draining water. If floor coverings are susceptible to moisture damage by moist floor conditions (capillary moisture), a vapor retarder should be placed below the slab-on-ground in accordance with the most recent addendum to ACI 302.1R-04 / 302.2R-06 and other current industry recommendations for use and placement of vapor retarders.

5.8 Excavations Adjacent to Existing Structures

Caution should be exercised when excavating immediately adjacent to existing structure foundations and the following should be considered.

The contractor should consider conducting excavations along the building structure perimeter footings in shorter segments (i.e., ≤ 10 feet in length parallel to existing foundation) and backfilling with properly compacted engineered fill with hand-held or smaller-sized equipment having a maximum pre-compacted thickness of 4 to 6 inches prior to moving to the next section.

When determined applicable, appropriate shoring techniques for existing structures and/or foundations should be utilized, and the contractor shall have the necessary project approval and experience in executing such activities.

Similarly, due to the proximity of the existing adjacent structures, larger compaction equipment vibrations may disturb, crack or damage existing structural elements. The existing conditions of the structures should be documented before beginning earthwork operations.

5.9 Lateral Earth Pressure Parameters

Lateral earth pressures vary as a function of construction sequence, type of backfill and retained soil, the rigidity of the retaining structure and the magnitude of any surface loading, if any, including stresses induced by adjacent building or wall loads on the retained soils. Adjacent footings or other surcharge loads may also exert appreciable additional lateral pressures. The effect of surcharge loads should be added to the recommended earth pressures to determine total lateral stresses.

Excavated in-situ or imported soils should be approved, placed, and compacted as outlined in this report. Values provided for soil types encountered at the site that are prepared in accordance with this report are illustrated, however, actual parameters are dependent on bearing material exposed and/or placed during construction. Values are provided for guidance and should only be utilized by experienced engineers and designers.

Material Type	Total Unit Weight γ (pcf)	Angle of Friction ϕ (°)	Rankine Earth Pressure Coefficients		
			Active K_a	At-Rest K_o	Passive K_p
Clay w/ trace sand	90 to 110	5	0.84	0.91	1.19
Sandy Clay or Clayey Sand	110 to 115	15	0.58	0.74	1.69
Silty Sand	115 to 125	30	0.33	0.50	3.00
Washed Aggregate	90 to 105	35	0.27	0.43	3.69

All material to be considered retained backfill should extend a minimum distance of 0.5 times the wall height laterally from the heel of cantilever wall footings. In backfilling against the walls, care should be taken to prevent the backfill from being over compacted, as this could result in excessive lateral stresses against the walls. Heavy equipment should not operate within 5 feet of walls to prevent excess lateral earth pressures.

All retaining walls should be provided with a positive drainage system, so they are not subject to hydrostatic pressures. We recommend that a minimum one-foot-wide zone of free-draining washed aggregate be constructed adjacent to the back of the walls and extend down to a foundation drain (perforated drainpipe).

Washed aggregate should be placed in lifts no greater than 2 feet in thickness and compacted with a backhoe bucket or similar method. The washed aggregate should be placed using a separation geotextile at the interface between the remaining backfill material. The foundation drain should be positively graded to allow drainage of any water that may collect in the wall backfill.

6.0 CONSTRUCTION MONITORING

We recommend that all earthwork construction be monitored by an experienced engineering technician of AIMRIGHT. Monitoring should include site preparation, subgrade earthwork, engineered fill earthwork, structure foundation systems, conventional and/or structural slabs.

Monitoring will allow AIMRIGHT to confirm the soil conditions on site and evaluate the recommendations presented within this report. If at the time of construction, our recommendations are inappropriate for the project, monitoring will allow us to remediate the recommendations at that time to better serve the project.

Monitoring during construction will also allow for the testing of all construction materials for the project. This includes but is not limited to:

- ✓ subgrade inspection and density testing,
- ✓ structural area fill placement density testing,
- ✓ foundation bearing grade observations and testing,
- ✓ structural and reinforcing steel inspection,
- ✓ concrete testing, and
- ✓ asphaltic concrete testing, as applicable.

We recommend that AIMRIGHT be retained to provide these services based upon our current familiarity with the project subsurface conditions, and the provided intent of the geotechnical recommendations pertaining to the proposed development.

7.0 LIMITATIONS

The recommendations provided are based in part on project information provided to us and they only apply to the specific project and site discussed in this report. If our statements or assumptions concerning the location and design of this project contain incorrect information, or if additional information is available, you should convey the correct or additional information to us and retain us to review our recommendations. We can then modify our recommendations if they are inappropriate for the proposed project.

Regardless of the thoroughness of the geotechnical exploration, there is always a possibility that subsurface conditions will be different from those at a specific boring location and that conditions will not be as anticipated by the designers or contractors. In addition, the construction process may itself alter soil conditions. Therefore, experienced geotechnical personnel should observe and document the construction procedures used and the conditions encountered. Unanticipated conditions and inadequate procedures should be reported to the design team along with timely recommendations to solve the problems created. The conclusions and recommendations presented in this report were derived in accordance with standard geotechnical engineering practices and no other warranty is expressed or implied.



Google Earth

 APPROXIMATE BORING LOCATIONS

BORING LOCATION PLAN

PROJECT NO.: 13320723
SOURCE: Aerial Imagery/Provided Plan

PROJECT: Spavinaw 54-inch Lift Station
CLIENT: BKL, Inc.



Google Earth

 APPROXIMATE BORING LOCATIONS

BORING LOCATION PLAN

PROJECT NO.: 13320723
SOURCE: Aerial Imagery

PROJECT: Spavinaw 54-inch Lift Station
CLIENT: BKL, Inc.





PROJECT: Spavinaw 54-inch Lift Station
CLIENT: BKL, Inc. **PROJECT NO.:** 13320723
PROJECT LOCATION: 555 N Main St, Spavinaw, OK 74366
LOCATION: see Boring Location Plan **ELEVATION:** N/A
DRILLER: H. Wilson **LOGGED BY:** N. Engle **DRILLING RIG:** CME-550 ATV-Mounted
DRILLING METHOD: Rotary Continuous Flight Augers **DATE:** 7/28/23
DEPTH TO WATER > INITIAL: ∇ Dry **AT COMPLETION:** ∇ Dry **CAVING >** \subset None

LOG OF BORING B-1

This information pertains only to this boring and should not be interpreted as being indicative of the site.

Depth (feet)	Sampler Type	Description	Graphic	USCS Symbol	SPT N-value (bpf)	Groundwater	Moisture Content	% < #200	Liquid Limit	Plastic Limit	Plasticity Index
0		TOPSOIL - 2 inches			29						
1		AGGREGATE BASE medium dense, light gray, moist			14		23.8	43.9	32	16	16
2		CLAYEY SAND w/ gravel, chert/limestone fragments medium dense, medium grayish brown, moist		SC	13						
6		LIMESTONE hard, light gray, dry to moist			50/0.5						
Auger refusal encountered at 6 ft. Boring terminated at 6.042 ft.											



PROJECT: Spavinaw 54-inch Lift Station

CLIENT: BKL, Inc.

PROJECT NO.: 13320723

PROJECT LOCATION: 555 N Main St, Spavinaw, OK 74366

LOCATION: see Boring Location Plan

ELEVATION: N/A

DRILLER: H. Wilson

LOGGED BY: N. Engle

DRILLING RIG: CME-550 ATV-Mounted

DRILLING METHOD: Rotary Continuous Flight Augers

DATE: 7/28/23

DEPTH TO WATER> INITIAL: ∇ Dry

AT COMPLETION: ∇ Dry

CAVING> \subset None

LOG OF BORING B-2

This information pertains only to this boring and should not be interpreted as being indicative of the site.

Depth (feet)	Sampler Type	Description	Graphic	USCS Symbol	SPT N-value (bpf)	Groundwater	Moisture Content	% < #200	Liquid Limit	Plastic Limit	Plasticity Index
0		TOPSOIL - 6 inches									
0.5		AGGREGATE BASE medium dense, light and medium gray, moist			21						
1.5		CLAYEY SAND w/ gravel, chert/limestone fragments medium dense, medium grayish brown, moist		SC	10		11.9	39.1	30	15	15
3					11						
4											
5											
6				SC	16		9.0	39.2	30	15	15
7											
8											
9					13						
10											
11		CLAYEY SAND w/ gravel, chert/limestone fragments very loose, dark brown, moist		SC	3		15.6	41.1	30	16	14
12											
13											
14		CLAYEY SAND w/ gravel, chert/limestone fragments medium dense, dark and medium brown, moist			13						
15											
16		LIMESTONE hard, light gray, dry to moist			50/0.25						
		Auger refusal encountered at 16.25 ft. Boring terminated at 16.25 ft.									

KEY TO SYMBOLS

Symbol Description

Strata Symbols



Topsoil



Aggregate Base



Clayey Sand



Limestone

Misc. Symbols



Auger Refusal

Soil Samplers



Standard Penetration Test