



CASE 1
COLLAR SHALL EXTEND TO TOP OF CONCRETE (REBAR REQ.)

CASE 2
COLLAR SHALL EXTEND 3" BELOW BOTTOM OF LOWEST GRADE RING (REBAR REQ.)

CONCRETE MANHOLE COLLAR DETAIL
CIRCULAR
NOT TO SCALE

NOTES: CONCRETE MANHOLE COLLARS ARE REQUIRED FOR ALL NEW AND REHABILITATED MANHOLES LOCATED IN THE PAVED AREAS AND SHALL BE BROUGHT TO FINISH GRADE WITH CONCRETE. COLLARS SHALL NOT BE USED IN UNPAVED AREAS OR FOR RAISED MANHOLES. REFER TO SPECIFICATIONS 416.3.12 FOR MORE DETAILS AND PAYMENT INFORMATION.

CONCRETE MANHOLE COLLAR FOR ASPHALT ROADS	
CITY OF TULSA, OKLAHOMA	
DRAWN BY: D.J.N. CHECKED BY: <i>tgp</i> DATE: MAY 2026	APPROVED <i>T. J. Sobel</i>
NOT TO SCALE	STANDARD NO. 409B

PATH NAME: /E1/PARTS/STD/DGN.STDS/409B-CONC-MH-COLLAR.DGN D.J.N. 4/30/2026